



ADHOC ACETATO

range size grain total substance
50x70 LG 217

face material Transparent cellulose acetate film available in gloss and matt version.

technical features standard/instrument unit of measure	substance	thickness	elongation at break	
	ISO 536	ISO 534		
	g/m ²	µm	%	
			long	cross
MATT	65	50	20	45
GLOSS	65	50	20	45

adhesive Permanent acrylic adhesive in water-based emulsion. Adhesive for plastic films. Good adhesion to non-polar surfaces. The perfect transparency makes it ideal for making “no label look” labels.

technical features unit of measure	tack	minimum cohesion	application temperature	minimum service temperature	maximum service temperature
	g/25 mm	hours	°C	°C	°C
SUPERTACK	900	15	+ 10	- 10	+ 100

backing material Single glazed and monosilicone coated white papers. Available in box version only, without crack-back.

technical features standard/instrument unit of measure	substance	thickness	tensile strength	
	ISO 536	ISO 536	ISO 1924	
	g/m ²	µm	N/15 mm	
			long	cross
	135	130	110	65

notes Special runs for sizes and/or other adhesives available upon request.

The Company reserves the right to modify the technological features of the product in relation to market requirements.



Adhoc Acetato is a self-adhesive product ideal for labels in cosmetic and pharmaceutical industries. The perfect transparency of the adhesive makes this product ideal for “no label look” applications. Not suited for applications requiring external use.

applications

Can be used without problems with the main conventional printing systems; good results in the main cutting and die-cutting operations.

general informations

The macro-porous surface suggests the use of inks for plastics. The self-adhesive product requires stable temperature and relative humidity conditions (20-22 °C and 50-55% U.R); for a good storage we suggest to pile the sheets (on pallet) at a maximum height of 1 meter and do not stack pallets.

If it is necessary to cut the sheets for the printing, we suggest to use a very sharp guillotine blade with an angle next to 20°, cutting piles of a maximum height of 30 mm at a time, and using the lowest pressure possible in order to prevent adhesive bleed. Acetate cut better face down. In the event of processing interruptions, protect the material against changes in temperature and humidity by wrapping it in polyethylene.

The shelf-life of a self-adhesive product is closely related, besides to storage conditions, to the nature of the adhesives and of the front materials used. At recommended storage conditions, the shelf-life is guaranteed for 18 months.

shelf life