



ADHOC PATTY GLOSS

range size grain total substance
50x70 LG 182

face material One side coated woodfree white paper with high gloss finish.

technical features
standard/instrument
unit of measure

substance	thickness	brightness	opacity	gloss	tensile strength	
ISO 536	ISO 536	ISO 2470	ISO 2471	T 480	ISO 1924	
g/m ²	µm	%	%	%	long	cross
80	67	93	88	86	7,5	4,3

adhesive Removable modified acrylic adhesive in water-based emulsion. Adhesive for paper labels for general use. Good adhesion and removability on most surfaces. The degree of removability depends on the type of the surface and the method of application, therefore preliminary application test are recommended. Approved for indirect food contacts and corresponding to UNI EN 71 “toy security” norms.

technical features
unit of measure

tack	minimum cohesion	application temperature	minimum service temperature	maximum service temperature	
g/25 mm	ore	°C	°C	°C	
REMOVABLE	300	0,5	+ 5	- 10	+ 80

backing material Single glazed and monosilicone coated white papers. Available in box version, with or without crack-back.

technical features
standard/instrument
unit of measure

substance	thickness	opacity	tensile strength	
ISO 536	ISO 536	ISO 2471	ISO 1924	
g/m ²	µm	%	long	cross
85	92	84	70	40

notes Special runs for sizes and/or other adhesives available upon request.

The Company reserves the right to modify the technological features of the product in relation to market requirements.



Adhoc Patty Gloss is a common used self-adhesive product. Ideal for multicolour printings when are required exceptional contrast and great detail.

applications

Can be used without problems with the main conventional printing systems; good results in the main cutting and die-cutting operations. The self-adhesive product requires stable temperature and relative humidity conditions (20-22 °C and 50-55% U.R); for a good storage we suggest to pile the sheets (on pallet) at a maximum height of 1 meter and do not stack pallets. If it is necessary to cut the sheets for the printing, we suggest to use a very sharp guillotine blade with an angle next to 20°, to cut the piles of a maximum height of 30 mm at a time, and using the lowest pressure possible in order to prevent adhesive bleed.

general
informations

The shelf-life of a self-adhesive product is closely related, besides to storage conditions, to the nature of the adhesives and of the front materials used. At recommended storage conditions, the shelf-life is guaranteed for one year.

shelf life