



# ADHOC PATTY MATT

<b>range</b>	size	grain	total substance
	50x70	LG	192
	70x100	SG	192

**face material** One side coated woodfree white paper with matt finish.

<b>technical features</b> standard/instrument unit of measure	substance	thickness	brightness	opacity	tensile strength	
	<i>ISO 536</i>	<i>ISO 536</i>	<i>ISO 2470</i>	<i>ISO 2471</i>	<i>ISO 1924</i>	
	<i>g/m<sup>2</sup></i>	<i>µm</i>	<i>%</i>	<i>%</i>	<i>Kg/15 mm</i>	
					<i>long</i>	<i>cross</i>
	90	88	93	91	8,6	4,7

**adhesive** Modified acrylic adhesive in water-based emulsion. Adhesive suited to a wide range of applications, featuring high tack and adhesion values as well as good processing properties. Approved for indirect foodcontacts and corresponding to UNI EN 71 “toys security” norms.

<b>technical features</b> unit of measure	tack	minimum cohesion	application temperature	minimum service temperature	maximum service temperature
	<i>g/25 mm</i>	<i>hours</i>	<i>°C</i>	<i>°C</i>	<i>°C</i>
<b>SUPERTACK</b>	1200	3	+ 5	- 10	+ 80

**backing material** Single glazed and monosilicone coated white papers. Available in box or bulk packed versions with or without crack-back.

<b>technical features</b> standard/instrument unit of measure	substance	thickness	opacity	tensile strength	
	<i>ISO 536</i>	<i>ISO 536</i>	<i>ISO 2471</i>	<i>ISO 1924</i>	
	<i>g/m<sup>2</sup></i>	<i>µm</i>	<i>%</i>	<i>N/15 mm</i>	
				<i>long</i>	<i>cross</i>
	85	92	84	70	40

**notes** Special runs for sizes and/or other adhesives available upon request.

The Company reserves the right to modify the technological features of the product in relation to market requirements.



Adhoc Patty Matt is a common used self-adhesive product. Ideal for multicolour printings when are required exceptional contrast and great detail.

applications

Can be used without problems with the main conventional printing systems; good results in the main cutting and die-cutting operations. The self-adhesive product requires stable temperature and relative humidity conditions (20-22 °C and 50-55% U.R); for a good storage we suggest to pile the sheets (on pallet) at a maximum height of 1 meter and do not stack pallets. If it is necessary to cut the sheets for the printing, we suggest to use a very sharp guillotine blade with an angle next to 20°, to cut the piles of a maximum heigh of 30 mm at a time, and using the lowest pressure possible in order to prevent adhesive bleed.

general  
informations

The shelf-life of a self-adhesive product is closely related, besides to storage conditions, to the nature of the adhesives and of the front materials used. At recommended storage conditions, the shelf-life is guaranteed for 18 months.

shelf life