



ADHOC FLUO

range size grain total substance
50x70 LG 182

face material One side coated fluorescent paper, with matt finish. High colour depth and uniformity, very good formation and clarity. Available in four colours: yellow, orange, fuchsia and green.

technical features standard/instrument unit of measure	substance	thickness	opacity	tensile strength	
	ISO 536	ISO 536	ISO 2471	ISO 1924	
	g/m ²	µm	%	Kg/15 mm	
				long	cross
	82	75	100	6,3	3

adhesive Modified acrylic adhesive in water-based emulsion. Adhesive suited to a wide range of applications, featuring high tack and adhesion values as well as good processing properties. Approved for indirect foodcontacts and corresponding to UNI EN 71 “toys security” norms.

technical features unit of measure	tack	minimum cohesion	application temperature	minimum service temperature	maximum service temperature
	g/25 mm	hours	°C	°C	°C
SUPERTACK	1200	3	+ 5	- 10	+ 80

backing material Single glazed and monosilicone coated white papers. Only available in box version with crack-back.

technical features standard/instrument unit of measure	substance	thickness	opacity	tensile strength	
	ISO 536	ISO 536	ISO 2471	ISO 1924	
	g/m ²	µm	%	N/15 mm	
				long	cross
	85	92	84	70	40

notes Special runs for sizes and/or other adhesives available upon request.

The Company reserves the right to modify the technological features of the product in relation to market requirements.

Adhoc Fluo is a common used self-adhesive product. Ideal for promotional or decorative labels.

applications

Can be used without problems with the main conventional printing systems; good results in the main cutting and die-cutting operations. The self-adhesive product requires stable temperature and relative humidity conditions (20-22 °C and 50-55% U.R); for a good storage we suggest to pile the sheets (on pallet) at a maximum height of 1 meter and do not stack pallets. If it is necessary to cut the sheets for the printing, we suggest to use a very sharp guillotine blade with an angle next to 20°, cutting piles of a maximum height of 30 mm at a time, and using the lowest pressure possible in order to prevent adhesive bleed.

**general
informations**

The shelf-life of a self-adhesive product is closely related, besides to storage conditions, to the nature of the adhesives and of the front materials used. At recommended storage conditions, the shelf-life is guaranteed for 18 months.

shelf life