



STUCCO COROLLA LABEL

description Laid papers made with E.C.F. pulp, with “Stucco” processing on one side. This feature ensures extraordinary printing results. Wet-strength. Available in Premium White and Ivory colours.

range size grain substance
72x101 LG 85

technical features
standard/instrument
unit of measure

substance	VSA	opacity	cobb 60*	W.B.R.	breaking length	
ISO 536	ISO 534	ISO 2471	ISO 535	ISO 3781	ISO 1924	
g/m ²	cm ³ /g	%	g/m ²	%	m	
					long±10%	cross±10%
85 ± 3%	1,30	89 ± 2	22 ± 3	≥ 20	5500	3600

Relative Humidity 50% ± 5
*Wire side

treatment



ecological features



ELEMENTAL
CHLORINE
FREE
GUARANTEED



notes The product is completely biodegradable.
Special runs available upon request.

The Company reserves the right to modify the technological features of the product in relation to market requirements.




Stucco Corolla Label has been specially developed for the label sector to exploit the features of laid products together with printing performance of a coated media. The particular wet-strength treatment makes this paper ideal for a wide variety of applications in bottling when returnable/recyclable bottles are used.

applications


For labelling, always observe the correct indications as regards grain direction. It must be parallel to the base of the bottle (see drawings).

Form of the label




wrap-around label

Rolling after wetting the back of the label.



correct grain direction



wrong grain direction

Can be used without problems with the main printing systems: letterpress, offset, blind embossing, hot foil stamping, thermography, screen printing and bronzing.

In offset printing the macro-porous surface requires the use of oxidative drying inks.

printing suggestions

Good results with major processing operations such as: cutting, die-cutting and glueing.

converting suggestions